

Upward Opening Access Door

- DOOR: 18 gauge cold rolled steel
- FRAME: 16 gauge cold rolled steel
- HINGE: Concealed continuous piano
- LATCH: 1/4 Allen head key
- FINISH: Gray powder paint
- INSULATION: Non-combustible, high temperature
- CERTIFICATION: Warnock-Hersey listed for 2 hrs

FIRE-RATED 

HORIZONTAL ONLY 

CUSTOM SIZING 





BIUA2436

BIUA or BFRU

WIDTH			X	HEIGHT			OPTIONS	
STANDARD SIZES (WIDTH & HEIGHT)				STANDARD SIZES (WIDTH & HEIGHT)			OPTIONS	
12 x 12	18 x 18	22 x 36		24 x 48	30 x 36	32 x 32	B	Bonderized / galvanized
14 x 14	22 x 22	24 x 36		30 x 30	30 x 48	36 x 36	G	Gasketing
							S	T304 Stainless steel

Custom sizes are available. Use IUA for access doors 24 x 36 or smaller; FRU for larger doors. Rough opening is door size + 1/4.

Medium Security Access Door

- DOOR: 12 gauge cold rolled steel
- FRAME: 12 gauge cold rolled steel
- HINGE: Concealed continuous piano
- FINISH: Gray powder paint

SECURITY 

CUSTOM SIZING 



BMTM1818

BM	FLANGE		LATCH		WIDTH		X	HEIGHT		OPTIONS	
	STANDARD SIZES (WIDTH & HEIGHT)		STANDARD SIZES (WIDTH & HEIGHT)		STANDARD SIZES (WIDTH & HEIGHT)			STANDARD SIZES (WIDTH & HEIGHT)		OPTIONS	
T	1 Flange	M	Mortise lock (1-1/8) prep	8 x 8	16 x 16	22 x 30	30 x 36	B	Bonderized / galvanized		
W	Drywall bead	P	Pinned allen head cam latch(es)	10 x 10	16 x 20	24 x 24	32 x 32	G	Gasketing		
P	Plaster casing	S	Pinned allen head security screw(s)	12 x 12	18 x 18	24 x 30	36 x 36	M	Masonry anchors		
				12 x 18	18 x 24	24 x 36	36 x 48	S	T304 Stainless steel		
				12 x 24	20 x 30	24 x 48					
				14 x 14	22 x 22	30 x 30					

Custom sizes are available. Rough opening is door size + 1/4.