

Fire-Rated Security Access Door

DOOR: 14 gauge cold rolled steel
 FRAME: 16 gauge cold rolled steel
 HINGE: ST: Flush continuous piano
 SW/SP: Concealed pin
 FINISH: Gray powder paint
 INSULATION: 2 thick fire rated mineral fiber
 CERTIFICATION: UL listed B label for 1-1/2 hrs

- FIRE-RATED 
- SECURITY 
- VERTICAL ONLY 
- CUSTOM SIZING 
- 



BSTK1212

BS

FLANGE

LATCH

WIDTH

 X

HEIGHT

OPTIONS

FLANGE	
T	1 Flange
W	Drywall bead
P	Plaster casing

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8) prep



STANDARD SIZES (WIDTH & HEIGHT)		
12 x 12	22 x 30	24 x 40
16 x 16	24 x 24	24 x 48
18 x 18	24 x 36	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing
M	Masonry anchors
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4.

Draft Stop Access Door

DOOR: 14 gauge cold rolled steel (self-closing)
 FRAME: 16 gauge cold rolled steel
 HINGE: Flush continuous piano
 FINISH: Gray powder paint

- VERTICAL ONLY 
- CUSTOM SIZING 



BDTK2230

BD

FLANGE

LATCH

WIDTH

 X

HEIGHT

OPTIONS

FLANGE	
T	1 Flange
W	Drywall bead

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8) prep

STANDARD SIZES (WIDTH & HEIGHT)		
22 x 36	24 x 60	36 x 36
24 x 36	30 x 30	36 x 48
24 x 48	30 x 36	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4.